



FLOOR

- Available dimensions: 9' / 9.5' / 11' / 11.5'
- Material: 10 gauge Brinell 150
- Side to floor angle 22° with fixed side or flat floor with drop sides
- Outside width 99"
- Four "D"-rings installed (one in each corner)

UNDERSTRUCTURE

- Crossmemberless structure
- Longmember configuration: formed 8"
- Longmember material: 3/16" Brinell 150
- Adjustable mud flap brackets mounted at rear

SIDE

- Available dimensions: 14"
- Material: 10 gauge Brinell 150
- Available configurations: fixed or drop sides
- Open profile top rail
- Drop side mounted to edge of body, closes without preparatory cleanup

HEADSHEET & CAB SHIELD

- Material: 10 gauge Brinell 150
- 10" cab shield available at 49" (53" with sub-frame)
- Headsheet configurations: flat for underbody hoist with 4" subframe
- Window slots in headsheet
- Optional manual tarp

TAILGATE

- Available dimensions: 19"
- Material: 10 gauge Brinell 150
- Double acting tailgate
- Spreader chains included

HOIST CONFIGURATION

- Patent Pending Brandon Underbody hoist with 4" bolt-on sub-frame for quick installation (Brackets provided)
- Optional double acting electric power pack including oil tank and controls
- Optional electrical truck battery breaker and cables

FINISHING OPTIONS

- Sandblasted, primed, and painted with black heavy-duty epoxy