



FLOOR

- Available dimensions: 8'6" to 12'
- Material: 10 gauge Brinell 150, 3/16" Brinell 150, 3/16" Brinell 450
- Side to floor angle 22° with fixed side or flat floor with drop sides
- Outside width: 99"
- Four "D"-rings installed (one in each corner)

UNDERSTRUCTURE

- Crossmemberless structure
- Longmember configuration: formed 8"
- Longmember material: 3/16" Brinell 250
- Adjustable mud flap brackets mounted at rear

SIDE

- Available dimensions: 14"
- Material: 10 gauge Brinell 150, 3/16" Brinell 150, 3/16" Brinell 250
- Available configurations: fixed or drop sides
- Open profile top rail standard
- Drop side mounted to edge of body, closes without preparatory cleanup

HEADSHEET & CAB SHIELD

- Material: 10 gauge Brinell 150, 3/16" Brinell 150, 3/16" Brinell 250
- 10" cab shield available at 49" (53" with sub-frame), 53" in height (57" with sub-frame) or 57" in height (61" with sub-frame)
- Headsheet configurations: flat for underbody hoist
- Optional window slots in headsheet
- Optional 3/4" light holes for cab shield
- Optional manual tarp

TAILGATE

- Available dimensions: 19"
- Material: 10 gauge Brinell 150, 3/16" Brinell 150, 3/16" Brinell 250
- Standard manual double acting tailgate
- Spreader chains included
- Optional bolt-on single centered coal door

HOIST CONFIGURATION

- Patent Pending Brandon Underbody hoist with 4" bolt-on sub-frame for quick installation (Brackets provided)
- Optional double acting electric power pack including oil tank and controls
- Optional electrical truck battery breaker and cables

FINISHING OPTIONS

- Sandblasted, primed, and painted with black heavy-duty epoxy