



FLOOR

- Available dimensions: 8' 6" to 18'
- Material: 10 gauge Brinell 150 (up to 12'), 3/16" Brinell 150, 3/16" Brinell 450, 1/4" Brinell 450
- Side to floor angle 22º with fixed side or flat floor with drop sides
- · Outside width: 99"
- Optional 96" (fixed sides)
- Four "D"-rings installed (one in each corner)

UNDERSTRUCTURE

- Crossmemberless structure
- · Longmember configuration: formed or I-beam 6", 8" or 10"
- · Longmember material: 3/16" Brinell 250
- Adjustable mud flap brackets mounted at rear

SIDE

- Available dimensions: 14" to 18" (drop sides), 14" to 20" (fixed sides)
- Material: 10 gauge Brinell 150, 3/16" Brinell 150, 3/16" Brinell 250
- · Available configurations: fixed or drop sides
- Open profile top rail standard optional closed profile
- Drop side mounted to edge of body, closes without preparatory cleanup
- Optional wood board brackets
- Standard removal center post starting over 12' in length with double drop sides

HEADSHEET & CAB SHIELD

- Material: 10 gauge Brinell 150, 3/16" Brinell 150, 3/16" Brinell 250
- 10" to 18" cab shield installed or loose − variable heights available
- · Headsheet configurations: flat for underbody hoist or recessed for front mount telescopic
- Optional window slots in headsheet
- Optional 3/4" light holes for cab shield
- · Optional manual tarp

TAILGATE

- Available dimensions: 19" to 25"
- Material: 10 gauge Brinell 150, 3/16" Brinell 150, 3/16" Brinell 250
- · Standard manual double acting tailgate with optional air tailgate latch system
- · Spreader chains included
- Optional bolt-on single centered coal door

HOIST CONFIGURATION

- · Choice of Patent Pending Brandon underbody hoist with 4" bolt-on sub-frame for quick installation (Brackets provided) for 12' and under in length or front mount telescopic hoist (single or double acting) for 8' 6" to 16' in length
- · Optional double acting electric power pack including oil tank and controls (underbody hoist option only)
- Optional electrical truck battery breaker and cables (underbody hoist option only)
- · Optional front mount hoist installation kit

FINISHING OPTIONS

- · Sandblasted and primed
- Sandblasted, primed, and painted with heavy-duty epoxy (various colors available)









